SAC1264

Low Noise Amplifier Hermetically Sealed Module
0.5~4GHz **Rev 1.0**

Features

- Frequency: 0.5 ~ 4 GHz
- Gain: 47dB
- Noise Figure: 1.0dB Typ.
- Gain Flatness: ±1.5dB
- Supply Voltage: +12V
- Supply Current: 300mA

Typical Applications

- Radar and ECM
- RF/ Microwave Radio
- Military and Space
- Test and Measurement
- Fiber Optics

General Description

SAC1264 is a low noise amplifier Hermetically Sealed module with a typical small signal gain of 47dB Max and a nominal $OP_{-1}dB$ of 27dBm.

Electrical Performance

Parameter	Min.	Typ.	Max.	Units
Frequency Range		0.5 ~ 4		GHz
Gain	39	—	47	dB
Input VSWR	—	1.5	1.8	:1
Output VSWR	—	1.5	1.8	:1
Noise Figure	—	1.0	1.5	dB
Output Power for 1 dB Compression ($OP_{-1}dB$)	26	27	—	dBm
Supply Voltage	—	12	—	V
Supply Current (I_D)	—	300	400	mA

Mechanical Outline

All dimensions are in millimeters



RoHS

SuperApex, LLC
2801 Lakeside Drive, Suite 208, Bannockburn, IL 60015, USA
Tel: 1-847-505-8319, 1-847-573-9866
E-mail: sales@superapexco.com
Website: www.superapexco.com