

SAC1316

Absorptive SP2T Switch Module 6~12GHz

Rev1.0

Features

- Frequency: 6~12 GHz
- Insertion Loss: 1.5 dB
- Isolation: 80 dB
- SW Speed: 150 ns
- DC Power Supply @+5V/-5V: 80mA

Typical Applications

- Radar and ECM
- RF/ Microwave radio
- Military and Space
- Test and Measurement

General Description


SAC1316 is an absorptive SP2T switch module manufactured using microwave hybrid integration technology. The operating frequency from 6 to 12 GHz with 1.5 dB of insertion and 80 dB of isolation.

Electrical Performance

Parameter	Min.	Typ.	Max.	Units
Frequency Range	6	—	12	GHz
Insertion Loss	—	1.5	2.0	dB
Isolation	80	—	—	dB
VSWR	—	—	1.5	:1
P-0.1db	—	30	—	dBm
SW Speed	—	—	150	ns
DC Power Supply @+5V/-5V	—	—	80	mA
Operation Temp	-20	—	+60	°C
Storage Temp	-40	—	+85	°C

Mechanical Outline

All dimensions are in millimeters



E1	E2	
0	1	J0-J1
1	0	J0-J2
+3.3-5V		
00-0.5V		

SuperApex Corporation

1580 S. Milwaukee Ave., Suite 405, Libertyville, IL 60048, USA
Tel: 1-847-505-8319, 1-847-573-9866
E-mail: sales@superapexco.com
Website: www.superapexco.com