

SAC1283

Wide-band Amplifier Module 2~18GHz

Rev1.0

Features

- Frequency: 2~18 GHz
- Gain: 25dB
- Noise Figure: 6.5 dB
- Supply Voltage: +14V~+17V
- Supply Current: 450mA

Typical Applications

- Radar and ECM
- RF/ Microwave Radio
- Military and Space
- Test and Measurement
- Fiber Optics

General Description


SAC1283 is a wide-band amplifier manufactured using microwave hybrid integration technology. The operating frequency from 2 to 18 GHz with 25 dB of gain and 27 dBm Output P_{-1dB}.

Electrical Performance

Parameter	Min.	Typ.	Max.	Units
Frequency Range	2~18			GHz
Gain	25	—	—	dB
Gain Flatness		±2	—	dB
Input VSWR	—	1.7	2	:1
Output VSWR	—	1.7	2	:1
Noise Figure	—	6.5	7.5	dB
Output Power for 1 dB Compression (OP _{-1dB})	27	—	—	dBm
Supply Voltage	14	—	17	V
Supply Current (I _D)	—	450	550	mA

Mechanical Outline

All dimensions are in millimeters



all dimensions in mm

SuperApex, LLC

1580 S. Milwaukee Ave. Suite 405, Libertyville, IL 60048, USA
Tel: 1-847-505-8319, 1-847-573-9866
E-mail: sales@superapexco.com
Website: www.superapexco.com