SAC3934Q3

GaAs MMIC Driver Amplifier
0.05~3GHz 24dBm

Rev 1.0

Features

- Frequency：0.05~3GHz
- Gain：13dB
- Output P_{-1}dB: 24dBm
- Single Power Supply: +8V/200mA
- Output IP_3: 38dBm@3GHz
- Package Size：3mm×3mm×1.1mm

Typical Applications

- SDR
- High density MCM

General Description

SAC3934Q3 is a GaAs MMIC Driver Amplifier, which operates between in 0.05~3GHz.

The driver amplifier can provide 13dB of gain, 24dBm of output P_{-1}dB while requiring 200mA from a +8V supply voltage.

SAC3934Q3 is assembled in a 3mm x 3mm QFN plastic package.

Picture



Electrical Performance (T_A=25℃, V_D=+8V, I_D=200mA, Z_0=50Ω)

Parameter	Min.	Typ.	Max.	Units
Frequency Range		0.05~3		GHz
Small Signal Gain	11	13	16	dB
Gain Flatness	—	±0.75	±1.5	dB
Reverse Isolation	—	-19	—	dB
Input/Output VSWR	—	1.75	2.3	: 1
Noise Figure	—	3	5	dB
Output P_{-1}dB	23	24	—	dBm
Output IP_3	—	38*	—	dBm
Supply Current (I_D)	—	200	280	mA
Supply Voltage (V_D)	8	—	12	V

*Pin/Tone=13dBm fc=3GHz, △f=4MHz

Absolute Maximum Ratings

Maximum Input Power	+20dBm, CW 1min	Operating Temperature	-55℃~+85℃
Channel Temperature	150℃	Storage Temperature	-55℃~+150℃
Maximum V_D	12.5V		

SuperApex, LLC
2801 Lakeside Drive, Suite 208, Bannockburn, IL 60015, USA
Tel: 1-847-505-8319, 1-847-573-9866
E-mail: sales@superapexco.com
Website: www.superapexco.com

Typical Performance Curve

V_D=+8V，I_{DQ}=200mA, the following curves are taken from SAC3934Q3 evaluation board. No De-embedding operation has been Implemented.

Gain (dB) vs. Temperature



Reverse Isolation(dB) vs. Temperature



Input VSWR(:1) vs. Temperature



Output VSWR(:1) vs. Temperature



OP_{-1}dB(dBm) vs. Temperature



OIP_3(dBm) vs. Temperature





Outline Drawing

(All dimensions in mm)



Application Circuit



Pin Function

Pin No.	Description	Pin No.	Description
1	RF input, DC Coupled	7	Connect to ground
2	Connect to ground	8	Connect to ground
3	Connect to ground	9	RF input/Bias, DC Coupled
4	Connect to ground	10	NC or connect to ground
5	Connect to ground	11	NC or connect to ground
6	Connect to ground	12	NC or connect to ground

SuperApex, LLC
2801 Lakeside Drive, Suite 208, Bannockburn, IL 60015, USA
Tel: 1-847-505-8319, 1-847-573-9866
E-mail: sales@superapexco.com
Website: www.superapexco.com

SAC3934Q3 Evaluation Board



The Evaluation board is a 2-layer board fabricated using Rogers 4350 t=0.254 and using best practices for high frequency RF design. The RF input and RF output traces have a 50 Ω characteristic impedance.

Components List

Reference Des.	Value	Part Number	Manuf.
C1、C2、C3、C5	300pF	GRM1555C1H301JA	Murata
C4, C6	1uF	GRM0336R61A105KE	Murata
L1, L2	-	MMZ1005A222	TDK

Attention:

1. The moisture resistant grade of products is 2a, the storage environment ≤30° C/60% RH，the surrounding workshop Life is 4 weeks. 2. After un-packing, it is necessary to bake the parts for 6 hours in 125+/-5-degree environment before soldering.

SuperApex, LLC
2801 Lakeside Drive, Suite 208, Bannockburn, IL 60015, USA
Tel: 1-847-505-8319, 1-847-573-9866
E-mail: sales@superapexco.com
Website: www.superapexco.com